
Preferred Abrasives, Inc.

MATERIAL SAFETY DATA SHEET



·	riease rate consist	ent with INFFA		
SECTION I - NAME AND PRODUCT				
MANUFACTURER'S	CONTACT			
Preferred Abrasives, Inc.				
ADDRESS (CITY, STATE, AND ZIP	EMERGENCY TELEPHONE			
66 Industry Court Unit B Troy, Ohio 45373	937-332-8855			
TRADE NAME. COMMON NAME. OR SPECIFICATION	APPROVED BY:	Thomas Gulker		
Bore Polishers, Zirc	DATE:	Jan. 3, 2021		
CHEMICAL FAMILY OR PRODUCT TYPE ANY A metal mandrel with abrasive flaps attached.				

		SECTION	ON II - C	OMPOSITION			
					OSHA		CARCIN-
CHEMICAL NAME	%	COMMON NAME	REG*	CAS	PERMISSIVE	ACGIH	OGEN
			(Y/N)	#	EXPOSURE LIMIT	TLV	(Y/N)
ALUMINUM OXIDE	15-18	ALPHA ALUMINA	Υ	1344-28-1	15mg/M3	5mg/M3	N
Al2O3		(Abrasive Grain)			(Total Dust)	(Total Dust)	
ZIRCONIA OXIDE	10-12	ZIRCONIA(NZ, ZF, ZS)	N	1314-23-4	5mg/M3	5mg/M3	N
ZrO2					(as Zr)	(as Zr)	
Duroplastic Phenol or	70-75	Inert or Nuisance Dust	Υ	N/A	15mg/M3	5mg/M3	N
Urea Resin binder,					(Total Dust)	(Total Dust)	
& Inert Backing							

^{*}Maximums are required by OSHA 29 CPR 1910.1200 Hazard Communication Standard.

**Please note that steel, aluminum, and/or die cast hardware may be incorporated in this product. These portions in no way represent a hazard when handled in accordance with the measures set below	JW.
SECTION III - PHYSICAL AND CHEMICAL DATA	

	OLOTIO	IN III - I III OIOAL	THE OTTENION		
BOILING POINT	N/A	MELTING POINT	N/A	SPECIFIC GRAVITY	N/A
VAPOR PRESSURE	N/A	PERCENT VOLATILE BY	VOL. N/A	VAPOR DENSITY	N/A
EVAPORATION RATE	N/A	SOLUBILITY IN WATER	N/A	SOLUBILITY IN ALCOHOL	N/A
SOLUBILITY IN OTHER SOLVENTS			APPEARANCE AND OD	OR	
N/A			A metal mandre	with abrasive flaps attach	ed.
SE	ECTION I	V - FIRE AND EX	(PLOSION HAZA	ARD DATA	
FLASH POINT N/A		(METHOD USED)	N/A	FLAMMABLE LMTS. N/A	
EXTINGUISHING MEDIA	Water, Ca	rbon Dioxide, Foam,	Dry Chemical		
SPECIAL FIRE FIGHTING PROCEDU	JRE	Fiber and resin binde	er will burn or decon	npose; use respiratory protection	n.
EXPLOSION POTENTIAL	N/A				
SE	CTION V	' HEALTH, FIRS	TAID AND MEDI	CAL DATA	
PRIMARY ROUTES	ACUTE AND	CHRONIC HEALTH EFF	ECTS	FIRST AID AND	
OF ENTRY	AND EFFECTS OF OVEREXPOSURE MEDICAL INFORMATION				
INHALATION	ACUTE-	May cause coughing	, shortness of breath	Remove to fresh air; obtain first	st-aid or
Airborne dust during grinding	CHRONIC-	May effect breathing	capacity	medical assistance as ne	eded
INGESTION	Dust - no	o known adverse	effects,	First aid or medical assist	tance
Dust during grinding	ingestio	n not recommend	ed	as needed	
SKIN	Not abso	orbed through ski	n - may cause	First aid or medical assist	tance
During grinding	abrasion	ı in use		as needed	
EYE	Dust may irritate eyes Wash with water; first aid or		or		
Airborne dust during grinding				medical assistance as ne	eded
OTHER HEALTH RISKS	On some	e materials, eleva	ted sound levels	Obtain medical assistanc	e as
During grinding	may be	created which ma	y effect hearing	needed	

SECTION VI - CORROSIVITY AND REACTIVITY DATA STABILITY: UNSTABL STABLE POLYMERIZATION: MAY OCCUR WILL NOT OCCUP INCOMPATIBILITY (MATERIALS TO AVOID): N/A DECOMPOSITION PRODUCTS: In use, dust and decomposing resin fumes are generated. In most cases, the material removed from

work piece will be significantly greater than the coated abrasive product components. CONDITIONS TO BE AVOIDED:

N/A

SECTION VII - STORAGE HANDLING AND USE PROCEDURES

NORMAL STORAGE AND HANDLING:

Handle with adequate ventilation. See OSHA 29 CFR 1910.94 (ventilation) and OSHA 29 CFR 1910.1000 (air contaminants)

NORMAL USE:

Handle with adequate ventilation; See OSHA 29 CFR 1910.94 (ventilation), OSHA 29 CFR 1910.1000 (air contaminants), OSHA CFR 1910.213 (P) Sanding Machines & OSHA CFR 1910.243 STEPS TO BE TAKEN IN CASE OF LEAKS OR SPILLS:

Normal clean-up procedures.

TRANSPORTATION:

There are no chemicals included in final product that appear as a "hazardous material" as indicated in the Department of Transportation's document 49 CFR doc 172.101 App. A.

WASTE DISPOSAL METHOD:

Standard landfill methods consistent with applicable Federal, State, and local laws.

SECTION VIII - PERSONAL PROTECTION INFORMATION		
RESPIRATORY PROTE	CTION (SPECIFY TYPE) As needed, approved dust respirator OSHA 24 CFR 1910.134	
VENTILATION	LOCAL Recommended	
X	MECHANICAL Recommended (GENERAL)	
	OTHER NAIF	
PROTECTIVE GLOVES	Recommended when in use.	
EYE PROTECTION	Recommended OSHA 29 CFR 1910.133 (Face and Eye Protection)	
OTHER EQUIPMENT	As needed, hearing protection OSHA 29 CFR 1910.215 (Hearing Protection)	

See Sections VI, VII, and VIII

MEASURES TO BE TAKEN DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT THAT HAS BEEN IN CONTACT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Slight formaldehyde or phenolic resin odor from binding system may be released during storage.

OTHER PRECAUTIONS

N/A

N/A = NOT APPLICABLE NAIF= NO APPLICABLE INFORMATION FOUND

FOR COMPANY USE

The information and recommendations set forth herein are taken from sources believed to be accurate as of the date hereof, however, Preferred Abrasives, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the suitability of the recommendations, and assumes no liability to any user thereof.