Preferred Abrasives, Inc.

MATERIAL SAFETY DATA SHEET



	Ficase rate consist	CIT WILLINITA	
SECTION I - NAME AND PRODUCT			
MANUFACTURER'S	CONTACT		
Preferred Abrasives, Inc.	TECHNICAL D	EPARTMENT	
ADDRESS (CITY, STATE, AND ZIP	EMERGENCY TELEPHON	E	
66 Industry Court Unit B Troy, Ohio 45373	(937) 332-850	0	
TRADE NAME. COMMON NAME. OR SPECIFICATION	APPROVED BY:	Thomas Gulker	
Unitized Wheels - AO	DATE:	Jan. 3, 2021	
CHEMICAL FAMILY OR PRODUCT TYPE ANY			
Deurring Wheels, Abrasive, Aluminum Oxide Wheels			

		SECTION	ON II - C	OMPOSITION			
					OSHA		CARCIN-
CHEMICAL NAME	%	COMMON NAME	REG*	CAS	PERMISSIVE	ACGIH	OGEN
			(Y/N)	#	EXPOSURE LIMIT	TLV	(Y/N)
ALUMINUM OXIDE	35-45	ALPHA ALUMINA Y 1344-28-1 15mg/		15mg/M3	5mg/M3	N	
Al2O3		(Abrasive Grain)			(Total Dust)	(Total Dust)	
Binder System	20-30	Inert or Nuisance Dust	Υ	N/A	15mg/M3	5mg/M3	N
					(Total Dust)	(Total Dust)	
Backing, nylon	15-25	(as dust)	Y	N/A	15mg/M3	5mg/M3	N
		(ac add)	·		(Total Dust)	(Total Dust)	
						1	

^{*}Maximums are required by OSHA 29 CPR 1910.1200 Hazard Communication Standard.

**Please note that steel, aluminum, and/or die cast hardware may be incorporated in this product. These portions in no way represent a hazard when handled in accordance with the measures set below
SECTION III - PHYSICAL AND CHEMICAL DATA

SECTION III - PHYSICAL AND CHEMICAL DATA					
BOILING POINT	N/A	MELTING POINT	N/A	SPECIFIC GRAVITY	N/A
VAPOR PRESSURE	N/A	PERCENT VOLATILE BY	YVOL. N/A	VAPOR DENSITY	N/A
EVAPORATION RATE	N/A	SOLUBILITY IN WATER	N/A	SOLUBILITY IN ALCOHOL	N/A
SOLUBILITY IN OTHER SOLVENTS			APPEARANCE AND ODG	DR .	
N/A			Non-woven nylon fib	er solid wheel with abrasive cor	mponent
SE	ECTION	IV - FIRE AND EX	(PLOSION HAZA	RD DATA	
FLASH POINT N/A		(METHOD USED)	N/A	FLAMMABLE LMTS. N/A	
EXTINGUISHING MEDIA	CO2, foar	-			
SPECIAL FIRE FIGHTING PROCEDU		Fiber and resin bind	er will burn or decom	pose; use respiratory protection	n.
EXPLOSION POTENTIAL	N/A				
SECTION V HEALTH, FIRST AID AND MEDICAL DATA					
PRIMARY ROUTES	ACUTE AND	ACUTE AND CHRONIC HEALTH EFFECTS		FIRST AID AND	
OF ENTRY			MEDICAL INFORMATION		
INHALATION	ACUTE-	ACUTE- May cause coughing, shortness of breath		th Remove to fresh air; obtain first-aid or	
Airborne dust during grinding	CHRONIC-	May effect breathing	g capacity	medical assistance as ne	eeded
INGESTION	Dust - n	o known adverse	effects,	First aid or medical assis	tance
Dust during grinding	ingestio	n not recommend	led	as needed	
SKIN	Not absorbed through skir		n - may cause	First aid or medical assistance	
During grinding	abrasion in use			as needed	
EYE	Dust may irritate eyes			Wash with water; first aid or	
Airborne dust during grinding				medical assistance as ne	eded
OTHER HEALTH RISKS	On some materials, elevat		ated sound levels	ls Obtain medical assistance a	
During grinding	mav be	created which ma	av effect hearing	needed	

SECTION VI - CORROSIVITY AND REACTIVITY DATA STABILITY: UNSTABL STABLE POLYMERIZATION: MAY OCCUR WILL NOT OCCUP INCOMPATIBILITY (MATERIALS TO AVOID): N/A DECOMPOSITION PRODUCTS:

In use, dust and decomposing resin fumes are generated. In most cases, the material removed from work piece will be significantly greater than the coated abrasive product components.

CONDITIONS TO BE AVOIDED:

N/A

SECTION VII - STORAGE HANDLING AND USE PROCEDURES

NORMAL STORAGE AND HANDLING:

Handle with adequate ventilation. See OSHA 29 CFR 1910.94 (ventilation) and OSHA 29 CFR 1910.1000 (air contaminants)

NORMAL USE:

Handle with adequate ventilation; See OSHA 29 CFR 1910.94 (ventilation), OSHA 29 CFR 1910.1000 (air contaminants), OSHA CFR 1910.213 (P) Sanding Machines & OSHA CFR 1910.243 STEPS TO BE TAKEN IN CASE OF LEAKS OR SPILLS:

Normal clean-up procedures.

TRANSPORTATION:

There are no chemicals included in final product that appear as a "hazardous material" as indicated in the Department of Transportation's document 49 CFR doc 172.101 App. A.

WASTE DISPOSAL METHOD:

Standard landfill methods consistent with applicable Federal, State, and local laws.

SECTION VIII - PERSONAL PROTECTION INFORMATION		
RESPIRATORY PROTEC	CTION (SPECIFY TYPE) As needed, approved dust respirator OSHA 24 CFR 1910.134	
VENTILATION	LOCAL Recommended	
X	MECHANICAL Recommended (GENERAL)	
	OTHER NAIF	
PROTECTIVE GLOVES	Recommended when in use.	
EYE PROTECTION	Recommended OSHA 29 CFR 1910.133 (Face and Eye Protection)	
OTHER EQUIPMENT	As needed, hearing protection OSHA 29 CFR 1910.215 (Hearing Protection)	

See Sections VI, VII, and VIII

MEASURES TO BE TAKEN DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT THAT HAS BEEN IN CONTACT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Slight formaldehyde or phenolic resin odor from binding system may be released during storage.

OTHER PRECAUTIONS

N/A

N/A = NOT APPLICABLE NAIF= NO APPLICABLE INFORMATION FOUND

FOR COMPANY USE

The information and recommendations set forth herein are taken from sources believed to be accurate as of the date hereof, however, Preferred Abrasives, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the suitability of the recommendations, and assumes no liability to any user thereof.